

**Product Data Sheet**

**Application:** HVAC

# ISOVER CLIMCOVER ROLL ALU2



## HVAC - Thermal Insulation for Metal Ductwork

Isover CLIMCOVER Roll Alu2 can be considered for the thermal and acoustic insulation of circular metal ductwork. The strong, flexible and lightweight glass mineral wool rolls are easy to handle and feature an aluminium foil facing, which provides an inherent vapour barrier and a professional finish.

## Features and Benefits



### Thermal Performance

Offers energy savings through helping to control temperatures and reduce heat loss or gain within ductwork.



### Fire Classification

Achieves a Euroclass A2-s1,d0 Reaction to Fire classification, according to EN 13501-1.



### Acoustic Benefits

The fibre structure of glass mineral wool traps sound energy and dissipates it within its thickness, helping to improve the acoustic comfort of those living or working within the building.



### Sustainability

Manufactured from up to 82% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit [isover.co.uk/CSR](https://isover.co.uk/CSR).



### Easy to Install

Lightweight and offers a combination of flexibility and mechanical strength, allowing fast and efficient cutting and fitting.

# Key Considerations

When using Isover CLIMCOVER Roll Alu2 you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire.

Please refer to the following product documents:

- Declaration of Performance - available at [isover.co.uk/products/Isover-climcover-roll-alu2](https://isover.co.uk/products/Isover-climcover-roll-alu2)
- Safe Use Instruction Sheet - available at [isover.co.uk/healthandsafety](https://isover.co.uk/healthandsafety)

# Product Specification

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m <sup>2</sup> )	Rolls per pallet	Pallet area (m <sup>2</sup> )
5200625465	25	18.00	1.20	21.60	18	388.80
5200625467	40	12.00	1.20	14.40	18	259.20
5200625469	50	9.00	1.20	10.80	18	194.40

# Thermal Conductivity

Mean temp °C	10	40	50	100	120
Declared thermal conductivity (W/m.K)	0.032	0.037	0.039	0.049	0.054

# Characteristics

<b>Fire</b>	Euroclass A2-s1,d0 Reaction to Fire classification according to EN 13501-1.	<b>Certification</b>	UKCA Marked to EN 14303. CE marked to EN 14303. Designation code: MW-EN 14303-T3.
<b>Service Temperature</b>	Can be considered for continuous service temperatures from 5°C to 150°C. The temperature on the aluminium facing should not exceed 80°C. For applications over 150°C, please contact our Technical Support Centre. When using the product for the insulation of ductwork with a surface temperature below dew point, care must be taken to ensure a 100% vapour barrier is maintained.	<b>Quality</b>	All Isover products are manufactured under Quality Management Standard – ISO 9001. Please visit <a href="https://isover.co.uk/accreditations">isover.co.uk/accreditations</a> for further details.
<b>Environmental</b>	All Isover products are manufactured under Environmental Management System – ISO 14001. BES 6001 Rating “Good” - The Framework Standard for Responsible Sourcing. Please visit <a href="https://isover.co.uk/accreditations">isover.co.uk/accreditations</a> for further details.	<b>Handling, Storage, Health and Safety</b>	Information regarding storage, installation and handling of Isover products and health & safety information can be found at <a href="https://isover.co.uk/healthandsafety">isover.co.uk/healthandsafety</a> . Achieves a Eurofins Gold product status for indoor air quality (certificate available at <a href="https://isover.co.uk/Eurofins">isover.co.uk/Eurofins</a> ). EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit <a href="https://isover.co.uk/accreditations">isover.co.uk/accreditations</a> ).
<b>Recycled Content</b>	Manufactured from up to 82% recycled glass.		



**Isover**

Saint-Gobain Isover UK Limited,  
Saint-Gobain House, East Leake, Loughborough,  
Leicestershire, LE12 6JU.

**Customer Service -  
Order Placement and Enquiries**

Tel: 0800 0322 555  
Email: [isover.customerservice@saint-gobain.com](mailto:isover.customerservice@saint-gobain.com)

**Technical Support Team**

Email: [isover.technical@saint-gobain.com](mailto:isover.technical@saint-gobain.com)

**[isover.co.uk](http://isover.co.uk)**

Published date: 02 Aug 2024

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [isover.co.uk](http://isover.co.uk)

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.